X-SCOPIC


THE COMPACT, ADJUSTABLE LADDER

A range of telescopic ladders for indoor and outdoor use, which are easy to store and transport. Perfect for cleaning gutters, changing a light bulb, accessing the loft, etc. Comfortable thanks to the 40 mm ribbed and anti-slip rungs, and adjustable thanks to the height adjustment feature (partial extension possible). The 3.20 m and 3.80 m models are fitted with a stabiliser bar with anti-slip footpads for added safety.

Class	Household
Use frequency	Regular
Use	Flat surface
Main material	Aluminium
150 (kg)	150
2 (year)	2
Standard	EN 131-6
Decree	96-333



Lock indicator and soft-close system



Anti-slip footpads or stabiliser bar (depending on the model)



Stabiliser bar with anti-slip footpads (models over 3 metres)



Comfort handles for easy transport



Anti-slip footpads (models under 3 metres)



Ribbed and non slip rungs



End caps



260mm rung spacing





Extremely compact (storage and transport)

All rights reserved, non-contractual images.

- Safety feature: lock indicator. Close-down speed control system.
- Comfortable: XL ribbed and anti-slip rungs.
- Easy access: 26 cm spacing between rungs.
- Carrying handle.











X-SCOPIC

Reference		(cm)	(cm)	(cm)	(cm)	(cm)	(m)	(mm)	(kg)	
00094726	9	263	75	7	46,1		**3,5**	70	8,6	3178740200312
00094729	10	293	82	9	48		**3,8**	79	9,9	3178740200329
00094732	11	327	85	10	53	81	**4,1**	69	12	3178740200336
00094738	13	387	91	9	51	87	**4,7**	77	14,8	3178740200343

The stabiliser bar is supplied unassembled but comes with all the necessary screws and the instructions.

Number of rungs / steps	Max. height of deployed product (m)	Folded product height (m)	Thickness of folded product (m)	Product width without stabilisers (m)	Product width with stabiliser bar (m)	Max. access height (m)	Upright section (mm)	Weight (kg)	Barcode