

X-SCOPIC

COMPACT, ADJUSTABLE LADDER

Range of telescopic ladders for indoor and outdoor use that are easy to store and transport. These models are ideal to clean gutters, change a light bulb, access roof spaces, etc. Comfortable to use, with ribbed anti-slip rungs 40 mm wide and adjustable height (partial deployment possible). The 3.20 and 3.80 m models are fitted with a stabiliser bar with anti-slip footpads for enhanced safety.

Class	Household
Use frequency	Regular
Use	Flat surface
Main material	Aluminium
Maximum load (kg)	150
Guarantee (year)	2
Standard	EN 131-6
Decree	96-333



Lock indicator and soft-close system



Stabiliser bar with anti-slip footpads (models over 3 metres)



Comfort handles for easy transport



Anti-slip footpads (models under 3 metres)



Ribbed and non slip rungs



End caps



260mm rung spacing



Model presented: 00094729

- Secure: lock indicator. Soft-close mechanism.
- Comfortable: XL ribbed and non slip rungs
- Easy access: 26cm spacing between rungs
- Carrying handle



Extremely compact (storage and transport)

X-SCOPIC

Reference		 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (mm)	 (kg)	
00094726	9	2.63	0.75	0.07	0.46		3,5	70	8,6	3178740200312
00094729	10	2.93	0.82	0.09	0.48		3,8	79	9,9	3178740200329
00094732	11	3.27	0.85	0,1	0.53	0.81	4,1	69	12	3178740200336
00094738	13	3.87	0.91	0.09	0.51	0.87	4,7	77	14,8	3178740200343

The stabiliser bar is supplied unassembled, but with all the necessary screws and instructions.

	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (mm)	 (kg)	
Number of rungs / steps	Max. height of deployed product	Folded product height	Thickness of folded product	Product width without stabilisers	Product width with stabiliser bar	Max. access height	Upright section	Weight	Barcode