

MULTISCOPIC

THE DUAL-FUNCTION TELESCOPIC LADDER

The Multiscopic aluminium ladder is versatile for use in all circumstances. It is a lightweight, safe, and comfortable means of access.

Class	Professional
Use frequency	Intensive
Use	Flat surface / Uneven surface
Material	Aluminium
Maximum load (kg)	150
Guarantee (year)	2
Standard	EN 131-4
Decree	96-333



Robust steel hinges



Wide base for increased safety



Offset rungs



Rung locking system



Level offset use



Model shown: 00094319

- For use on flat surfaces and stairways
- Stability provided by the flared bases and the footpads
- Very easy-to-handle sliding section with a simple and reliable locking system




Construction finishing work



Maintenance



Model shown: 00094319



Level offset use



MULTISCOPIC

Reference		 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	(m)	(m)	 (kg)	
00094318	4x3	1.34	0.91	0.21	2.72	1.76	3.62	0.41	0.66	9,7	3178740234423
00094319	4x4	1.83	1.16	0.21	3.73	2	4.63	0.41	0.86	11,9	3178740234430
00094320	4x5	2.31	1.41	0.21	4.74	2.24	5.64	0.41	1.03	14,2	3178740234447

										
Number of rungs / steps	Max. overall product height (m)	Folded product height (m)	Thickness of folded product (m)	Max. height of deployed product (m)	Max. access height in step ladder position (m)	Max. access height (m)	Product width without stabilisers (m)	Overall width with stabilisers (m)	Weight (kg)	Barcode