

ARTIPLI

THE MULTI-FUNCTIONAL LADDER

This ladder can be used in four different positions: straight, as an access platform, double section and in ladder stand-off position. Perfect for all types of craftsmen.

Class	Professional
Use frequency	Intensive
Use	Flat surface
Material	Mixed aluminium/steel
Maximum load (kg)	150
Guarantee (year)	2
Standard	EN 131-4
Decree	96-333



Wide bases for increased stability



Removable steel platform



Robust steel hinges



Anti-slip steel platform



- Easy to deploy / fold thanks to pre-programmed positions
- Easy storage and transport: foldable and compact
- Anti-slip steel platform
- 260 mm spacing between rungs
- Four possible positions:
 1. Platform (max access height: 2.89 m)
 2. Double ladder (max access height: 2.52 m)
 3. Ladder stand-off (max access height: 3.29 m)
 4. Single-section ladder (max access height: 4.20 m)



ARTIPLI

Reference		 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	(m)	(m)	 (kg)	
00094514	4x3	1.62	0.92	0.28	3.3	2.52	4.2	0.35	0.76	12	3178740234454

18.3 kg with the detachable steel platform.

 Number of rungs / steps	 Max. overall product height (m)	 Folded product height (m)	 Thickness of folded product (m)	 Max. height of deployed product (m)	 Max. access height in step ladder position (m)	 Max. access height (m)	Product width without stabilisers (m)	Overall width with stabilisers (m)	 Weight (kg)	 Barcode
--	---	---	---	---	--	--	---------------------------------------	------------------------------------	---	---