2-SECTION MANUAL SLIDE STARLINE

THE CLASSIC DOUBLE LADDER!

The Starline two-section aluminium sliding ladder is equipped with a stabiliser bar with reinforced footpads, ensuring safety. Its lightweight also makes it easy to use.

Class	Household
Use frequency	Regular
Use	Flat surface
Main material	Aluminium
150 (kg)	150
3 (year)	3
Standard	EN 131
Decree	96-333
Recyclable up to (%)	94




Rungs secured by non-removable, non-deformable crimping



Stabilising base with anti-slip footpads



Locks to secure the sliding platform



24 x 24 mm square, ribbed, anti-slip rungs



28 cm spacing between rungs



Model shown: 00122708

MADE IN FRANCE

All rights reserved, non-contractual images.

- Ultra-resistant: rungs are fastened by non-removable, non-deformable crimping. Rectangular mouldings 20 mm wide.
- Stable: stabilising base with anti-slip footpads.
- Secure: locks to hold the sliding section in place.
- Comfortable: 24 x 24 mm square rungs with ribbed and non slip.
- Easy access: 28 cm spacing between rungs.

2-SECTION MANUAL SLIDE STARLINE

Reference		(m)	(m)	(m)	(m)	(m)	(m)	(m)	(mm)	(kg)	
00122708	2x8	2.28	3.68	**2.17**	**4.58**	0.13	0.39	0.71	61 / 61	7.2	3178740265199
00122710	2x10	2.85	4.81	**2.17**	**5.71**	0.15	0.39	0.81	78 / 78	10.2	3178740265205
00122712	2x12	3.41	5.93	**2.17**	**6.82**	0.15	0.39	1.01	78 / 78	12.2	3178740265212

The stabilising base is delivered unassembled but with screws and the instructions.

Number of rungs / steps

Folded product height (m)

Max. height of deployed product (m)

Min. access height (m)

Max. access height (m)

Thickness of folded product (m)

Product width without stabilisers (m)

Overall width with stabilisers (m)

Upright section (mm)

Weight (kg)

Barcode