

PRONOR SINGLE

A MUST FOR PROFESSIONALS

This Pronor aluminium single ladder has 30 x 30 mm rungs that guarantee comfort and durability.

Class	Professional
Use frequency	Intensive
Use	Flat surface
Material	Aluminium
Maximum load (kg)	150
Guarantee (year)	5
Standard	EN 131
Decree	96-333
Recyclable up to (%)	92



Ribbed non-slip footpads (models < 3m)



Ultra-strong rungs through double expansion crimping



Non-slip ribbed footpads (models < 3m)



Base for increased stability (models > 3m)



Models shown: 01210508 / 01210512

- Uprights are designed for safe handling
- Rungs 30 x 30mm



All rights reserved, non-contractual images.

PRONOR SINGLE

Reference		 (m)	 (m)	 (m)	 (m)	 (mm)	 (kg)	
01210508	8	2.4	3.3	0.35	0.35	56	3.5	3178740185473
01210509 ☹	9	2.68	3.58	0.35	0.35	56	4	3178740185480
01210510	10	2.96	3.86	0.35	0.35	56	4.5	3178740185497
01210512	12	3.52	4.42	0.35	0.71	66	6.5	3178740162276
01210514	14	4.1	5	0.35	0.81	66	7.4	3178740162283
01210516 ☹	16	4.66	5.56	0.35	0.91	66	8.4	3178740162290
01210518	18	5.22	6.12	0.35	0.91	79.50	11	3178740162306

☹ Reference on request

	 (m)	 (m)	 (m)	 (m)	 (mm)	 (kg)	
Number of rungs / steps	Max. overall product height (m)	Max. access height (m)	Product width without stabilisers (m)	Product width with stabiliser bar (m)	Upright section (mm)	Weight (kg)	Barcode