

PRONOR 2-SECTION PUSH-UP

Easy-of-use for meeting all your requirements

The Pronor aluminium manual double extension ladder can reach up to 9.14 metres. Its slot-in pads, 30 x 30 mm rungs and safety locking guarantee reliability in all environments. It complies with the EN 131 standard and decree 96-333. It has the NF, GS and VGS quality labels.



- For quick safe work at high levels.
- Sections are accurately guided in sturdy extruded aluminium runners.
- Wide base for increased stability (+ 3. m models).
- +3m models: Additional base with reinforces footpads



Ribbed non-slip footpads



Product characteristics

Use	Intensive
Use	Flat floor
Max access / working height (m)	9,17
Material	Aluminium
Maximum load (kg)	150
Warranty (years)	5
Norms	EN 131
Decree	96333
NF Label //	

Ref.	Folded H (m)	Deployed Height (m)	Nb of steps	Weight	Width stabilizaters folded (m)	Width stabilizaters deployed (m)	Section	Max access Height (m)	Gencod
1222306	1,84	2,59	2x6	6,3	0,42	-	66	3,5	3178740186890
1222307	2,12	3,23	2x7	7	0,42	0,71	66	4,1	3178740162429
1222308	2,4	3,79	2x8	7,6	0,42	0,81	66	4,65	3178740162436
1222310	2,96	4,91	2x10	10,3	0,42	0,91	66	5,77	3178740162443
1222312	3,52	6,03	2x12	13,6	0,42	1,01	79	6,9	3178740162450
1222314	4,08	7,15	2x14	16,4	0,42	1,11	79	8,02	3178740162467
1222316	4,64	8,27	2x16	23,4	0,42	1,21	90	9,17	3178740162474