

PRONOR TWO-SECTION ROPE-OPERATED LADDER

THE ESSENTIAL MEDIUM-HEIGHT LADDER FOR PROFESSIONALS

The Pronor aluminium three-section combination ladder features cast aluminium joints, a flared base and a steel spreader arm guaranteeing reliability and comfort for all users.

Class	Professional
Use frequency	Intensive
Use	Flat surface
Material	Aluminium
Maximum load (kg)	150
Guarantee (year)	5
Standard	EN 131
Decree	96-333
Recyclable up to [%]	92



Locking pivot in cast aluminium (safe and accurate use)



Distance between rungs 280mm



Extension wheels Ø 100mm



Ribbed anti-slip footpads



For accessing alongside walls



Extension wheels Ø 100mm



Ultra-strong rungs through double expansion crimping



Model shown: 01232112

- Very easy to handle for installation
- Can be used alongside walls
- Short folded length for storage and transport
- Can be used to access really high levels
- Side stabilisers for greater stability
- Very strong moulded aluminium rung-lock catch
- Very good handle for installation
- Allows access to great heights
- Locking pivot in high-resistance cast aluminium



For accessing alongside walls



Adjustable stabilisers



Folding stabilisers for storage



PRONOR TWO-SECTION ROPE-OPERATED LADDER

Reference		(m)		(m)		(m)		(m)		(mm)		(kg)	
01232112	2x12	3.52	6.04	4.42	6.94	0.67	1.23	79	18,7	3178740186418			
01232113	2x13	3,8	6,6	4,7	7,5	0.67	1.23	79	19,5	3178740186425			
01232115	2x15	4.37	7.45	5.26	8.35	0.67	1.23	79	21,8	3178740186432			
01232116	2x16	4.65	8.01	5.56	8.91	0.67	1.23	90	24,2	3178740186449			
01232118	2x18	5.21	9.13	6.16	10.03	0.67	1.23	90	26,7	3178740186456			
01232120	2x20	5.77	9.97	6.67	10.87	0.67	1.23	90	29,2	3178740186463			
01232123	2x23	6.61	11.65	7.51	12.55	0.67	1.23	101	35,5	3178740186470			

									
Number of rungs / steps	Folded product height (m)	Max. height of deployed product (m)	Min. access height (m)	Max. access height (m)	Product width without stabilisers (m)	Overall width with stabilisers (m)	Upright section (mm)	Weight (kg)	Barcode