

PRONOR THREE-SECTION ROPE-OPERATED LADDER

THE PROFESSIONAL MODEL FOR HIGH-LEVEL WORK

The Pronor aluminium rope-operated ladder features three sections, slot-in pads, side stabilisers, 30 x 30 cm rungs and a cast aluminium rung-lock catch guaranteeing reliability and strength in all environments.

Class	Professional
Use frequency	Intensive
Use	Flat surface
Material	Aluminium
Maximum load (kg)	150
Guarantee (year)	5
Standard	EN 131
Decree	96-333
Recyclable up to [%]	92



Anti-slip footpads



Deployment rope



Ultra-strong rungs through triple expansion crimping



Model shown: 01233110

- Very easy to handle for installation
- Can be used alongside walls
- Short folded length for storage and transport
- Can be used to access really high levels
- Side stabilisers for greater stability
- Very strong moulded aluminium rung-lock catch
- Ladder sections slide easily thanks to polyamide runners (except 12- and 14-rung models)



PRONOR THREE-SECTION ROPE-OPERATED LADDER

Reference		(m)									
01233110	3x10	2.97	6.88	3.88	7.78		0.79	1.36	66/76/66	27.5	3178740186708
01233112	3x12	3.53	8.57	4.44	9.47	0.22	0.79	1.36	76/76.9/76	33.2	3178740186715
01233114	3x14	4.1	9.41	5	10.31	0.79	0.79	1.36	76/76.1/76	37.7	3178740186722
01233116	3x16	4.66	11.1	5.56	11.99		0.79	1.36	90/103/90	42.5	3178740186739
01233118	3x18	5.22	12.78	6.12	13.67		0.79	1.36	90/103/90	49.5	3178740186746

										
Number of rungs / steps	Folded product height (m)	Max. height of deployed product (m)	Min. access height (m)	Max. access height (m)	Thickness of folded product (m)	Product width without stabilisers (m)	Product width without stabilisers (m)	Upright section (mm)	Weight (kg)	Barcode