

PRONOR TWO-SECTION COMBINATION LADDER

THE ESSENTIAL VERSATILE LADDER FOR PROFESSIONALS

The Pronor aluminium two-section combination ladder features a flared base, cast aluminium joints and a steel spreader arm guaranteeing reliability and comfort.

Class	Professional
Use frequency	Intensive
Use	Flat surface / Uneven surface
Material	Aluminium
Maximum load (kg)	150
Guarantee (year)	5
Standard	EN 131
Decree	96-333
Recyclable up to [%]	92



Interlocking hooks and ribbed anti-slip footpads



Ultra-strong rungs through double expansion crimping



Rigid retaining bar for 8 and 10 rungs models



For flat and offset surfaces and stairways



Flared base for increased stability



30 x 30mm rungs




Opening with automatic positioning



Model shown: 01252008

- Lightweight and manoeuvrable for easy installation and transport
- 30 x 30 mm rungs for comfortable use
- Extreme rigidity with a reinforced ribbed moulded aluminium joint and a rigid spreader arm
- Versatile on flat surfaces and on stairs
- Multiple possible uses
- Freestanding
- Integrated level offset
- Moulded profiles for a good grip
- Flared base for perfect stability
- Steel spreader arms for safety
- Semi-circular anti-slip footpads



For flat and offset surfaces and stairways



PRONOR TWO-SECTION COMBINATION LADDER

Reference		(m)		(m)		(m)		(m)		(m)		(mm)		(kg)	
01252008	2x8	2.41	3.81	3.31	3.31	4.7	0.84	1.72	56	9.4	3178740187699				
01252009	2x9	2.7	4.38	3.59	3.59	5.26	0.84	1.9	66	10.8	3178740187705				
01252010	2x10	2.98	4.94	3.87	3.97	5.82	0.92	2.11	66	12	3178740187712				
01252012	2x12	3.54	6.06	4.43	4.43	6.95	1.02	2.56	79.50	15,5	3178740187729				
01252014	2x14	4.1	7.18	4.99	4.99	8.07	1.08	2.74	79.50	19	3178740187736				

The 12- and 14-rung models are fitted with straps and not safety bars

										
Number of rungs / steps	Folded product height [m]	Max. height of deployed product [m]	Max. overall product height [m]	Min. access height [m]	Max. access height [m]	Product width at base [m]	Base width [m]	Upright section [mm]	Weight [kg]	Barcode