


PRONOR 2-SECTION COMBINATION WITH BASE

THE ESSENTIAL VERSATILE LADDER FOR PROFESSIONALS

Class	Professional
Use frequency	Intensive
Use	Flat surface / Uneven surface
Main material	Aluminium
Maximum load (kg)	150
Guarantee (year)	5
Standard	EN 131
Decree	96-333
Recyclable up to (%)	91



Wide base for increased stability



Opening with automatic positioning



Interlocking hooks and ribbed anti-slip footpads



30 x 30mm rungs



Ultra-strong rungs through double expansion crimping



Model shown: 01252610

- Extremely rigid with a reinforced ribbed hinge in cast aluminium
- Lightweight and easy to erect and transport
- Stable with its wide base



Finishing decoration painting



Maintenance



Construction finishing work



PRONOR 2-SECTION COMBINATION WITH BASE

Reference												
		(m)	(m)	(m)	(m)	(m)	(m)	(m)	(m)	(mm)	(kg)	
01252608 ☹	2x8	2.43	3.83	2.23	3.33	4.73	0.18	0.81	1.61	66	9,5	3178740188405
01252610 ☹	2x10	2.99	4.95	2.75	3.89	5.85	0.18	0.91	2	66	11,5	3178740188429
01252612 ☹	2x12	3.55	6.07	3.28	4.45	6.97	0.21	1.01	2.39	79,5	15,5	3178740188436
01252614 ☹	2x14	4.11	7.19	3.8	5.01	8.09	0.21	1.11	2.77	79,5	18	3178740188443

Models fitted with straps and not with safety arms

☹ Reference on request

											
Number of rungs / steps	Folded product height (m)	Max. height of deployed product (m)	Max. overall product height (m)	Min. access height (m)	Max. access height (m)	Thickness of folded product (m)	Product width with stabiliser bar (m)	Base width (m)	Upright section (mm)	Weight (kg)	Barcode