

BASIC ALUMINIUM LADDER WITH STEPS

The most comfortable single ladder

This especially robust aluminium ladder provides maximum safety for its users thanks to its wraparound pads and 80 mm steps. Available with 7 to 13 steps for totally safe work at heights of up to 4.40 metres. In addition, the ladder complies with the EN 131 standard and decree 96-333 and has the NF, GS and VGS quality labels.



- : Light weight aluminium alloy.
- : Outsized uprights for increased stability and reinforced rigidity.
- : Wide non-slip steps for increased comfort.
- : Small gap between steps for easier access (25 mm).



Outsized uprights
79 mm



Ribbed non-slip
footpads

Product characteristics	
Use	Ultra intensive
Use	Flat floor
Max access / working height (m)	3,9
Material	Aluminium
Maximum load (kg)	150
Warranty (years)	5
Norms	EN 131
Decree	96333
NF Label //	

Ref.	Deployed Height (m)	Support H (m)	Wall gap	Nb of steps	Weight	Width stabilizers folded (m)	Section	Max access Height (m)	Gencod
02210107	2	1.85	0,75	7	4,6	0,38	79	2,9	3178740185695
02210108	2.25	2.09	0,84	8	5,2	0,38	79	3,15	3178740185701
02210109	2.5	2.32	0,94	9	5,8	0,38	79	3,4	3178740185718
02210110	2.75	2.55	1,03	10	6,4	0,38	79	3,65	3178740185725
02210111	3	2.78	1,12	11	6,9	0,38	79	3,9	3178740185732