

TREKKER MINI

AGILE & COMPACT

This platform is the miniature telescopic version of TREKKER's range of ultra-mobile platforms. Agile and compact, this 2-3 rung workstation is easy to transport thanks to its compact size, light weight and carry handle.

Class	Professional
Use frequency	Intensive
Use	Flat surface / Level offset
Main material	Aluminium
Maximum load (kg)	150
Guarantee (year)	5
Standard	EN 131-7
Decree	2004-924



Telescopic sections



Non-slip aluminium platform floor




Anti-lifting hook



Rear transport wheels



Strong joints with secure folding system for transport



Guardrail with semi-automatic closing rails



Tool tray



Non-slip inward footpads



Carry handle



Access rungs



The Trekker range is easy to transport, store and use, even in confined spaces or busy environments: without compromising on safety!

- Folds and unfolds in 3 easy steps! Patented system.
- Fully foldable for compactness like no other.
- Optimised mobility thanks to their light weight, support strap and ergonomic handle.
- **Self-supporting**: no need for bulky stabilisers.
- Fitted with rungs.
- **Ultra-compact**, only 1.03 m when folded.



Maintenance



TREKKER MINI

Reference															
02274350	2/3	1.03	0,5	1,5	1,74	0,45	0,68	2.45	2.68	1,23	0,62	0,62	16,2	3178740264499	

													
Number of rungs / steps	Folded product height (m)	Thickness of folded product (m)	Min. height of deployed product (m)	Max. height of deployed product (m)	Min. platform height (m)	Max. platform height (m)	Min. working height (m)	Max. working height (m)	Base width (m)	Product width without stabilisers (m)	Overall width with stabilisers (m)	Weight (kg)	Barcode