

DOUBLE ACCESS

THE MUST-HAVE FOR WORKSITES


This double-sided aluminium step ladder features 85mm steps equipped with an anti-spread system that serves as a footrest for optimal comfort. Its so-called "open" profiles provide lightness and ease of handling.

Class	Professional
Use frequency	Intensive
Use	Flat surface
Main material	Aluminium
Maximum load (kg)	150
Guarantee (year)	5
Standard	EN 14183 / EN 131
Decree	96-333

Range EN 131 except for 2 steps standardised EN 14183.




Anti-pinch hinge system



High-safety grooved steps 80mm



2 versions available: with or without guardrails



Anti-slip footpads



Optional guardrail



Model shown: 02374844

- Double access step ladder, usable from both sides
- Upper spreader lock to step over obstacles
- Deep steps of 80mm
- Sturdy open-profile uprights that are easy to handle
- Fully foldable for minimal space
- Also available with ultra-compact folding guardrail



DOUBLE ACCESS

Reference		 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (mm)	 (kg)	
02374842	2	0.53	0.48	0.19	0.48	2.48	0.43	0.52	82	3,5	8711563284074
02374843	3	0.77	0.71	0.19	0.23	2.23	0.46	0,7	82	5,2	8711563284081
02374844	4	1.02	0.94	0.19	0.46	2.46	0.49	0.88	82	6,5	8711563284098
02374845	5	1.27	1.18	0.19	0,7	2,7	0.53	1.05	82	8	8711563284104
02374846	6	1.53	1.42	0.19	0.93	2.93	0.55	1.22	82	9,6	8711563284111
02374847	7	1.78	1.65	0.19	1.16	3.16	0.59	1,4	82	11,2	8711563284128
02374848	8	2.03	1.88	0.19	1,4	3,4	0.61	1.56	82	12,6	8711563284135
02374840	Front guardrail									2,1	8711563135819

The footrest is counted as a step.

										
Number of rungs / steps	Folded product height (m)	Max. overall product height (m)	Thickness of folded product (m)	Max. platform height (m)	Max. access height (m)	Product width without stabilisers (m)	Base width (m)	Upright section (mm)	Weight (kg)	Barcode