

THE EXTRA COMFORTABLE STEPLADDER

With its 110 mm wide steps, high-resistance single-piece composit hinges and reinforced uprights, KOLOS really stands out for its toughness and comfort. Kolos is certified NF.*



5-step model

- ▶ Crimped, non-slip steps in extruded aluminium, 110 mm wide
- ▶ Moulded and ribbed, high-resistance single-piece composit hinges.
- ▶ Tool-holder with integrated closing
- ▶ Platform 280 x 250 mm
- ▶ Footpads full-covering, non-slip pads with wear indicator
- ▶ Epoxy-painted uprights with high-resistance step fittings
- ▶ 2 black straps for 7 to 10 step models

Product characteristics

Use	Intensive
Type of floor	Flat floor
Max access / working height (m)	4,28
Material	Painted aluminium
Maximum load (kg)	150
Warranty (years)	5
Standard	EN 131
Decree	96333; Warenwet


*NF for Kolos from 3 to 8 steps.



Non-slip steps in extruded aluminium, 110 mm wide



One-piece hinges in ribbed, ultra-resistant cast aluminium



High resistant uprights



Straps for 7 to 10 step models




Optional ramp (ref: 02376450)



Tool-holder with integrated closing



High-security covering footpads



Epoxy-painted uprights

The platform is considered as a step. Delivered in plastic film. 7 to 10 steps models are equipped with straps.

Ref.	Folded H (m)	Platform H	Wheelbase (m)	Nb of rungs/steps	Weight (kg)	Product width at the base (m)	Access / work H (m)	EAN barcode
02375813	1,44	0,66	0,75	3	4,8	0,43	2,66	3178740203016
02375814	1,69	0,89	0,91	4	5,8	0,46	2,89	3178740203023
02375815	1,94	1,12	1,06	5	6,8	0,48	3,12	3178740203030
02375816	2,19	1,36	1,22	6	7,8	0,51	3,36	3178740203047
02375817	2,44	1,59	1,37	7	9	0,54	3,59	3178740203054
02375818	2,69	1,82	1,52	8	10,1	0,56	3,82	3178740203061
02375819	2,94	2,05	1,67	9	12,8	0,86	4,05	3178740243197
02375820	3,19	2,28	1,82	10	13,5	0,89	4,28	3178740243203