


PRESTO


SCAFFOLDING FOR ASSEMBLY IN A JIFFY

The Presto aluminium scaffold tower is quick and easy to assemble. Its wheel offset system enables work on all types of ground.

Class	Household
Use frequency	Regular
Use	Flat surface / Uneven surface
Material	Aluminium
Maximum load [kg]	150
Maximum load [kg/m ²]	150
Guarantee [year]	3
Standard	NF E 85-200



4 swivel wheels,
12.5cm diameter



Quarter-turn
systems with
integrated handle



Pre-assembled
structure (no tools
required)




Fabric tool holder



Foldable and
retractable
stabilisers (except
0.94m model)



Platform with 2
anti-lift hooks



Transport hatch
lock



Model shown: 02400417

- Easy to assemble: pre-assembled structure. No tools required. Quarter-turn systems with integrated handle.
- Ultra-fast assembly: 3 min for Presto 3 / 7 min for Presto 4.5 / 13 min for Presto 6.5.
- Reassuring: platform with 2 anti-lift hooks
- Stable: 4 stabilisers with anti-slip footpads (Presto 4.5 and Presto 6.5). Wheel brakes.



Platforms adjustable every 30 cm



Level offset possible



PRESTO

Reference	Nb of platform	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (kg)	 Extension kit 4.5m 02400457	 Extension kit 3m 02400455	
02400413 ⓘ	1	2	1,5	0.65	1,5	0.65	2	0.94	2.94	19,5	1	1	3178740189204
02400415	1	3,8	1,5	0.65	2.05	1.21	2	2.44	4.44	30	1	1	3178740189228
02400417 ⓘ	2	5,6	1,5	0.65	4,1	3.25	2	4.54	6.54	51	1	1	3178740189235

The 02400417 model is delivered in two packages.

ⓘ Reference on request

 Max. overall pro- duct height (m)	 Overall length without stabilisers (m)	 Product width without stabilisers (m)	 Overall length with stabilisers (m)	 Overall width with stabilisers (m)	 Folded height (m)	 Max. platform height (m)	 Max. working height (m)	 Weight (kg)	 Barcode
---	---	--	---	--	--	--	---	--	--