

FIRST 5

ALL THE FEATURES OF THE LARGER MODELS

The First aluminium scaffold tower. Practical, lightweight and safe, it is also easy to handle and quick to install.

Class	Household
Use frequency	Moderate
Use	Flat surface / Uneven surface
Material	Aluminium
Maximum load (kg/m²)	150
Guarantee (year)	2
Standard	NF E 85-200
Comfort level	2
Recyclable up to [%]	93



Model shown: 02400905

- The FIRST 5 is quick to assemble and install
- No tools or screws needed
- Movement is facilitated by two Ø100 mm castor wheels attached to one of the two stabiliser bars
- Platform locks
- Locking of cross-braces and braces with a quarter turn system
- Can be used with level offset
- Offset base for better stability



A scaffold tower for a variety of tasks



Work with level offset



All rights reserved, non-contractual images.

FIRST 5

Reference	Nb of platform	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (kg)	
02400905	1	3.79	1.71	0.65	1.21	2.06	0.2	0.61	0.28	2.43	2.3	4.43	23,7	3178740095055

 Max. overall product height without stabilisers (m)	 Overall length sers (m)	 Product width sers (m)	 Overall width with stabilisers (m)	 Folded height (m)	 Folded width (m)	 Folded length (m)	 Min. platform height (m)	 Max. platform height (m)	 Min. working height (m)	 Max. working height (m)	 Weight (kg)	 Barcode
--	---	--	--	---	--	---	--	--	---	---	--	--