

SPEEDY 4 PLUS

PRACTICAL, ECONOMICAL ALUMINIUM SCAFFOLDING

The Speedy Plus is an aluminium scaffold tower with a usable platform area of 147 x 57 cm. The folding base means it can be assembled rapidly and has a very small footprint, making it easy to transport. It also allows the Speedy Plus to be used with level offset. Its lightweight structure and overall dimensions make it particularly suitable for indoor use.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface / Uneven surface
Material	Aluminium
Maximum load (kg/m ²)	200
Guarantee (year)	5
Standard	EN 1004-1
Recyclable up to (%)	95



Folding base



Quick assembly without any tools



Braces guardrail



Castor wheels Ø 125mm



Compact folding base: 1.75 x 0.83 x 0.23m



To work on offset surfaces



Easy installation with ergonomic platform hooks



Model shown: pack 1 + 2 + 3 + 4

- Folding base for quick installation and easy storage
- The folding base can be removed to enable level offset
- Reinforced platforms
- Easy installation with ergonomic platform hooks
- Protection toe boards on the work platform whatever the height
- Product sold in packs that can be combined to reach each height
- Ø125 mm wheels with brakes
- Goes through 93 cm wide doors



SPEEDY 4 PLUS

Reference	Nb of platform	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (kg)	T one stabiliser 20400020	ASS base ladder 1 x 6 02408230	Cross-brace L 1.991 m 20400041	Wheel ID 125 mm 20400004	ASS toe boards 02408233	Speedy brace 02408204	ASS speedy 3 folding base 02408231	ASS speedy platform 02408232	ASS speedy 1x4 extension 02408227	A-S 7r Speedy 3 extension 02408223	
02408921	1	1.76	1.75	0.89	3.08	3.34	0.35	0,6	2,6	51,5	4	2	1	4	1	4	1	0	0	3178740235130
02408922					Pack 2				8,5	0	0	0	0	0	1	0	0	2	0	3178740235147
02408923					Pack 3				11,8	0	0	2	0	0	0	0	0	0	2	3178740235154
02408924					Pack 4				27,5	0	0	4	0	0	4	0	1	0	2	3178740235161

									
Max. overall product height (m)	Overall length without stabilisers (m)	Product width without stabilisers (m)	Overall length with stabilisers (m)	Overall width with stabilisers (m)	Min. platform height (m)	Max. platform height (m)	Max. working height (m)	Weight (kg)	Barcode