

PLATINIUM SINGLE-SECTION STRAIGHT LADDER

THE ESSENTIAL LADDER FOR FINISHING WORK

This Platinum aluminium single-section straight ladder features a stabiliser bar with footpads and reinforced uprights guaranteeing strength and stability.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface
Material	Aluminium
Maximum load (kg)	150
Guarantee (year)	5
Standard	EN 131
Decree	96-333
Recyclable up to [%]	92



Ultra-strong rungs through double expansion crimping



Ribbed anti-slip footpads (models < 3m)



30 x 30mm rungs



Base with reinforced footpads (models > 3m)



Models shown: 02410207 / 02410214

- Reliable and robust, very easy to handle
- Reinforced profiles with 30 x 30 mm rungs



All rights reserved, non-contractual images.

PLATINIUM SINGLE-SECTION STRAIGHT LADDER

Reference		 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (mm)	 (kg)	
02410206	6	1.85	2.75	1.73	0.63	0.36		66	3,2	3178740185299
02410207	7	2.13	3.03	2	0.73	0.36		66	3,7	3178740185305
02410208	8	2.41	3.31	2.26	0.82	0.36		66	4,1	3178740185312
02410210	10	2.97	3.87	2.79	1.02	0.36		66	5	3178740185329
02410212	12	3.56	4.46	3.35	1.22	0.36	0.81	66	6,2	3178740162207
02410214	14	4.12	5.02	3.88	1.41	0.43	0.91	66	7,5	3178740162214
02410216	16	4.68	5.58	4,4	1,6	0.43	0.91	66	8,4	3178740162221
02410217	17	4.96	5.86	4.67	1,7	0.43	1.01	79,50	9,7	3178740162238
02410220	20	5,8	6,7	5,46	1,99	0.43	1,11	79,50	11,3	3178740162252
02410224 ☉	24	6,92	7,82	6,51	2,37	0.43	1,11	79,50	13,4	3178740162269
02410206-002 ☉	6	1.85	2.75	1.74	0.63	0.36		66	3.55	3178740185374
02410207-002 ☉	7	2.13	3.03	2	0.73	0.36		66	4.05	3178740185381
02410210-002 ☉	10	2.97	3.87	2.79	1.02	0.36		66	5.35	3178740185398
09061002	Mooring bar								1,5	3178740099893

☉ Reference on request

									
Number of rungs / steps	Max. overall product height (m)	Max. access height (m)	Recommended positioning height (m)	Recommended wall distance (m)	Product width without stabilisers (m)	Product width with stabiliser bar (m)	Upright section (mm)	Weight (kg)	Barcode