

PLATINIUM TWO-SECTION PUSH-UP LADDER

THE LADDER FOR MEDIUM-LEVEL WORK

The Platinum aluminium push-up ladder has two sections. Its stabiliser bar with reinforced footpads, safety lock and extra-wide uprights guarantee safety and strength.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface
Material	Aluminium
Maximum load (kg)	150
Guarantee (year)	5
Standard	EN 131
Decree	96-333
Recyclable up to (%)	91

Produsenforskriften Certificate C901062. AFS 2004:3 Certificate C901061. SS 2091 edition 4
Certificate C901061. Tested and certified by RISE.



Wide base for increased stability



Ø 125mm extension wheels (12 to 18 rungs)



Moving section steel lock hooks



Sliding section locking



Model shown: 02422807

- Lightweight and easy to install
- Reinforced profiles with 30 x 30mm rungs
- Locking of the sliding section to ensure safety in the access position
- These models are very easy to install and can be used to reach medium heights very quickly
- Ribbed end fittings for better stability



All rights reserved, non-contractual images.

PLATINIUM TWO-SECTION PUSH-UP LADDER

Reference		(m)		(m)		(m)		(m)		(mm)		(kg)	
02422806	2x6	1,8	2.94	2.68	3.84	0.44	0.71	66	6,8	3178740169169			
02422807	2x7	2.08	3,5	2.96	4,4	0.44	0.71	66	7,7	3178740162351			
02422808	2x8	2.36	4.06	3.24	4.96	0.44	0.81	66	8,7	3178740162368			
02422810	2x10	2.92	4,9	3,8	5,8	0.44	0.91	66	10,5	3178740162375			
02422812	2x12	3.55	6.11	4.45	7.01		1.01	79,50	14,3	3178740162382			
02422814	2x14	4.11	6.95	5	7.85		1.11	79,50	16,4	3178740162399			
02422816 ☹	2x16	4.68	8.35	5.57	9.25		1.21	90	21,7	3178740162405			
02422818 ☹	2x18	5.24	9.19	6.12	10.9		1.21	90	23,9	3178740162412			

The ladders of the 6 to 10 rung models are detachable. The 12 to 18 rung models are fitted with castor wheels on the top.

☉ Reference on request

									
Number of rungs / steps	Folded product height (m)	Max. height of deployed product (m)	Min. access height (m)	Max. access height (m)	Product width without stabilisers (m)	Overall width with stabilisers (m)	Upright section (mm)	Weight (kg)	Barcode