


ALL-ALUMINIUM GRS

COMFORT AT THE HIGHEST LEVEL

This all-aluminium telescopic straight ladder has a guardrail, integrated toe boards and stabilisers to ensure a high level of safety. Handling is facilitated by two wheels for moving.


Class	Professional
Use frequency	Intensive
Use	Flat surface
Material	Aluminium
Maximum load (kg)	150
Guarantee (year)	2
Standard	NF E 85-211
Decree	2004-924
Recyclable up to (%)	86




Extremely powerful locking of the moving section



Intuitive guardrails set-up



Use leaning against a wall



Moving wheels Ø 175 mm





- This model is particularly comfortable: very wide access section and platform, large capacity tool holder
- The Ø175 mm wheels make it easy to position
- The guardrail automatically clicks into place very easily
- 389 x 420 mm wood platform with integrated toe boards



Maintenance



Construction finishing work



ALL-ALUMINIUM GRS

Reference													
02432108	8+5	3.16	0.34	3.95	4.16	4.95	2.16	2.95	1.5	0.91	2.22	25,6	3178740058050

												
Number of rungs / steps	Max. overall product height folded (m)	Thickness of product (m)	Max. height of deployed product (m)	Min. access height (m)	Max. access height (m)	Min. ascent height (m)	Max. ascent height (m)	Base width (m)	Product width without stabili- sers (m)	Overall width with stabilisers (m)	Weight (kg)	Barcode