

PLATINIUM 300 TWO-SECTION ROPE-OPERATED LADDER

THE IDEAL LADDER FOR WORKING AT HEIGHT

The Platinum 300 aluminium two-section rope-operated ladder sets the standard for rope-operated ladders on the market. Its adjustable side stabilisers, wrap-around footpads for enhanced safety and extra-wide uprights guarantee safety and strength.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface
Material	Aluminium
Maximum load (kg)	150
Guarantee (year)	5
Standard	EN 131
Decree	96-333
Recyclable up to (%)	90



Ultra-strong rungs through double expansion crimping



Ribbed anti-slip footpads



Extension wheels Ø 125mm



Orientated steps, foot rests flat



Folding stabilisers for compact storage



For accessing alongside walls



Automatic extruded aluminium locking pivot with insert in polyamide



Model shown: 02432310

- Very popular with roofers
- The crimped upright/rung connections are highly reliable to ensure maximum user safety
- The upper section is fitted with non-staining black positioning wheels to make it easier to use on facades
- The rope is an essential safety element for using this model (it is UV-resistant)
- High-safety maxi covering footpads guarantee ground contact in all situations
- 280mm spacing between rungs makes the product more lightweight and

easier to handle



All rights reserved, non-contractual images.

PLATINIUM 300 TWO-SECTION ROPE-OPERATED LADDER

Reference		(m)		(m)		(m)		(m)		(mm)		(kg)	
02432310	2x10	2.97	4.93	3.87	5.83	0.6	1.24	76	19.5				3178740162634
02432312	2x12	3.53	6.05	4.43	6.95	0.6	1.24	76	21.5				3178740162641
02432314	2x14	4.09	6.89	4.99	7.79	0.6	1.24	76	24				3178740162658
02432316	2x16	4.65	8.02	5.55	8.92	0.6	1.23	76	26.5				3178740162665
02432318	2x18	5.22	9.14	6.12	10.04	0.6	1.24	90	33.5				3178740162672
02432320	2x20	5.78	9.98	6.68	10.88	0.6	1.23	90	35				3178740162689
02432323 ☹	2x23	6.62	11.94	7.52	12.84	0.6	1.23	101	40				3178740162702

 Reference on request

									
Number of rungs / steps	Folded product height (m)	Max. height of deployed product (m)	Min. access height (m)	Max. access height (m)	Product width without stabilisers (m)	Overall width with stabilisers (m)	Upright section (mm)	Weight (kg)	Barcode