

PLATINIUM TWO-SECTION COMBINATION LADDER

THE UNRIVALLED COMBINATION LADDER

The Platinum aluminium two-section combination ladder sets the standard on the market with its flared base, wrap-around footpads for enhanced safety and a patented Quick Safe joint. It guarantees strength, versatility and safety for all its users.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface / Uneven surface
Main material	Aluminium
Maximum load (kg)	150
Guarantee (year)	5
Standard	EN 131
Decree	96-333
Recyclable up to (%)	91



Intuitive ribbed and semi-automatic hinges



Ultra-strong rungs through double expansion crimping



Easy opening (connections are highly reliable and extremely strong)



Flared base for increased stability



Distance between rungs 280mm (30 x 30mm rungs)



Extending section locking hooks



2 hooks on the upper section are placed on the rungs of the lower section



High-security covering footpads



Model shown: 02442610

- Designed to support highly-intensive use on all types of flooring.
- Exceptional performance in terms of strength, safety and comfort.
- Intuitive and automatic section deployment thanks to the Quick Safe system.
- The ultra-strong ribbed cast aluminium joint is virtually indestructible.
- Reinforced profiles for greater stability and durability.
- Models tested to support the demands of the most exacting professionals.
- Removable strap for unobstructed access on the 2x12 model



Construction finishing work



Finishing decoration painting



Maintenance



Structural work roofing



For flat and offset surfaces and stairways

PLATINIUM TWO-SECTION COMBINATION LADDER

Reference		 (m)	 (m)	 (m)	 (m)	 (m)	 (mm)	 (m)	 (m)	 (mm)	 (kg)	
02442606	2x6	1.8	2.92	1.66	2.7	3.82	200	0.69	1.28	66	7.8	3178740187446
02442607	2x7	2.08	3.48	1.93	2.98	4.38	200	0.77	1.47	66	8.9	3178740187453
02442608	2x8	2.36	4.04	2.19	3.26	4.94	200	0.85	1.66	66	10	3178740187460
02442609	2x9	2.64	4.6	2.45	3.54	5.5	200	0.85	1.86	66	10.8	3178740187477
02442610	2x10	2.92	4.88	2.71	3.82	5.78	200	0.93	2.05	66	12	3178740187484
02442612	2x12	3.48	6	3.25	4.38	6.9	200	1.02	2.44	79	16.3	3178740187491

											
Number of rungs / steps	Folded product height (m)	Max. height of deployed product (m)	Max. overall product height (m)	Min. access height (m)	Max. access height (m)	Thickness of folded product (m)	Product width at base (m)	Base width (m)	Upright section (mm)	Weight (kg)	Barcode