

ALL-ALUMINIUM FREESTANDING LADDER

BETWEEN THE MEANS OF ACCESS AND THE WORKSTATION

The all-aluminium freestanding ladder features a guardrail, platform and integrated toe boards.


Class	Professional
Use frequency	Intensive
Use	Flat surface
Material	Aluminium
Maximum load (kg)	150
Guarantee (year)	2
Standard	NF E 85-211
Decree	2004-924
Recyclable up to [%]	85



Tool holder



Sliding section lock



Use for work in false ceilings



Model shown: 02443200

- Freestanding product for work in false ceilings or cable trays
- Wrap-around footpads with wear indicator for enhanced safety
- Designed for work in the centre of rooms
- 389 x 373 mm platform with integrated toe boards
- Guardrail
- 175 mm wheels for moving



Maintenance



Construction finishing work



All rights reserved, non-contractual images.

ALL-ALUMINIUM FREESTANDING LADDER

Reference													
02443200	8+5	3.16	0.42	3.95	4.16	4.95	2.16	2.95	1.87	0.61	2.22	33,2	3178740093228

												
Number of rungs / steps	Max. overall product height folded (m)	Thickness of product (m)	Max. height of deployed product (m)	Min. access height (m)	Max. access height (m)	Min. ascent height (m)	Max. ascent height (m)	Base width (m)	Product width without stabilisers (m)	Overall width with stabilisers (m)	Weight (kg)	Barcode