

PLATINIUM THREE-SECTION COMBINATION LADDER

THE MUST-HAVE VERSATILE LADDER

The Platinum aluminium three-section combination ladder sets the standard on the market with its flared base, wrap-around footpads for enhanced safety and a patented Quick Safe joint. It guarantees strength, versatility and safety for all users.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface / Uneven surface
Main material	Aluminium
Maximum load (kg)	150
Guarantee (year)	5
Standard	EN 131
Decree	96-333
Recyclable up to (%)	92



Distance between rungs 280mm



Ultra-strong rungs through double expansion crimping



Extending section locking hooks



2 hooks on the upper section are placed on the rungs of the lower section



High-security covering footpads



Intuitive ribbed and semi-automatic hinges to facilitate opening. Connections are



Flared base for increased stability



3rd integral section for the 3x12-rungs model



Extending section locking hooks



30 x 30mm rungs



Model shown: 02443609

- The upper section is attached to the central section by two slides at the top and two hooks fitted with a safety lock at the bottom
- Detachable strap for unobstructed access
- Locking hooks for the sliding section



Construction finishing work




Finishing decoration painting



Structural work roofing



Maintenance



For flat and offset surfaces and stairways

PLATINIUM THREE-SECTION COMBINATION LADDER

Reference												
		(m)	(m)	(m)	(m)	(m)	(m)	(m)	(m)	(mm)	(kg)	
02443607	3x7	2.09	4.89	3.41	3	4.33	5.8	0.84	1.48	66	13,1	3178740187927
02443608	3x8	2.37	5.17	3.69	3.28	4.61	6.08	0.93	1.68	66	14,8	3178740187934
02443609	3x9	2.65	6.01	4.25	3.56	5.17	6.92	1.02	1.88	79,50	18,2	3178740187941
02443610	3x10	2.93	6.85	4.81	3.84	5.73	7.76	1,1	2.07	79,50	20	3178740187958
02443612	3x12	3.49	7.69	5.65	4.4	6.57	8.59	1.18	2.45	79,50	24,3	3178740187965

											
Number of rungs / steps	Folded product height (m)	Max. height of deployed product (m)	Product aerial height (m)	Min. access height (m)	Aerial access height (m)	Max. access height (m)	Product width at base (m)	Base width (m)	Upright section (mm)	Weight (kg)	Barcode