

EXCAVATION LADDER


THE NEW-GENERATION LADDER FOR ACCESS TO DEPTHS DOWN TO 4.75 M

This aluminium excavation ladder has 80 mm steps and a handrail guaranteeing that the user is perfectly safety. Its adjustable anti-tilt system stabilises the ladder in all situations.

Class	Professional
Usage	Ultra intensive
Utilisation	Flat surface / Level offset
Material	Aluminium
Charge maxi (kg)	150
Garantie (an)	5



Anti-slip steps
80mm



Swivel pads




Wheels for ease of
movement



Lifting rings



Height-adjustable
ladder



Telescopic
uprights for level
adjustment



- Ample space between guardrails at platform level for easier access
- Two handrails for total safety when climbing up or down
- A foldable platform to minimise storage space and facilitate transport
- Two wheels to make the moving the product easier
- Telescopic models to adapt to all worksites (foundations, site excavations, etc.)



EXCAVATION LADDER

Reference		 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (kg)	
02451306	6+4	3.13	0.41	3.13	1	1.95	1.52	0.62	21.2	3178740233648
02451308	8+7	4.06	0.42	4.06	1.47	2.88	1.9	0.62	25.2	3178740233655
02451312	12+12	5.91	0.42	5.91	2.39	4.73	2.57	0.62	32.6	3178740233662

 Number of rungs / steps	 Max. overall product height (m)	 Thickness of folded product (m)	 Max. height of deployed product (m)	 Min. ascent height (m)	 Max. ascent height (m)	 Base width (m)	 Product width without stabilisers (m)	 Weight (kg)	 Barcode
---	---	---	---	--	--	--	---	---	---