

PLATINIUM 500 TWO-SECTION ROPE-OPERATED LADDER

THE VERY BEST IN COMFORT AND SAFETY

The Platinum 500 aluminium ladder has two sections and a rope-operated extension system. Its adjustable side stabilisers, swivel footpads, reinforced uprights and angled rungs make this the highest-quality ladder on the market.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface
Material	Aluminium
Maximum load (kg)	150
Guarantee (year)	5
Standard	EN 131
Decree	96-333
Recyclable up to [%]	90



Anti-slip polyamide runners



Folding stabilisers for storage



Folding stabilisers for storage



For accessing alongside walls



Intuitive, safe height adjustment locking pivot



Stabilisers with anti-slip ribbed footpads



Orientated steps, foot rests flat



- Very popular with roofers
- The 30 x 30mm rungs have a flat surface under their feet for greater comfort
- 250mm spacing between rungs for greater comfort (knee on the 3rd rung)
- The footpad caps are drilled so that professionals can use a carpenter's nail to fix the ladder into the ground
- Easy to use with its rope-operated system (UV-treated rope)
- The ribbed profile of the uprights makes them easy to handle for precise installation
- Rungs are angled for providing a flat surface for standing on under the most

comfortable conditions

- The upper section is fitted with non-marking rubber guide wheels to facilitate deployment against a facade
- Rapid, intuitive stabiliser arrangement for increased stability
- The articulated shoes provide perfect stability for this very high ladder
- The soles on the footpads are drilled to enable professionals to nail the ladder to the ground if they so wish



Model shown: 02532311



All rights reserved, non-contractual images.

PLATINIUM 500 TWO-SECTION ROPE-OPERATED LADDER

Reference		(m)		(m)		(m)		(m)		(mm)		(kg)	
02532311	2x11	2.98	4.98	3.88	5.88	0,6	1.25	76	20,6	3178740162559			
02532313	2x13	3.48	5.98	4.38	6.88	0,6	1.25	76	23,1	3178740162566			
02532316	2x16	4.23	6.98	5.13	7.88	0,6	1.25	76	26,9	3178740162573			
02532318	2x18	4.72	7.98	5.63	8.88	0,6	1.25	76	29,4	3178740162580			
02532320	2x20	5.23	8.98	6.13	9.88	0,6	1.25	90	36,6	3178740162597			
02532322	2x22	5.73	9.98	6.63	10.88	0,6	1.25	101	41,4	3178740162603			

									
Number of rungs / steps	Folded product height [m]	Max. height of deployed product [m]	Min. access height [m]	Max. access height [m]	Product width without stabilisers [m]	Overall width with stabilisers [m]	Upright section [mm]	Weight [kg]	Barcode