


PLATINIUM 500 THREE-SECTION ROPE-OPERATED LADDER

THE ULTIMATE FOR HIGH-LEVEL WORK

The Platinum 500 aluminium ladder has three sections and a rope-operated extension system. Its swivel footpads, adjustable side stabilisers, reinforced uprights and angled rungs make this the highest-quality ladder on the market.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface
Material	Aluminium
Maximum load (kg)	150
Guarantee (year)	5
Standard	EN 131
Decree	96-333
Recyclable up to [%]	90



Interchangeable anti-slip caps



Extension wheels Ø 125mm



Orientated rungs, foot rests flat



Extension wheels Ø 125mm



Very strong rungs through triple expansion crimping



Oversized upright profiles for greater stability



Folding stabilisers for storage



Model shown: 02533311

- Very popular with roofers
- The 30 x 30mm rungs have a flat surface under their feet for greater comfort
- 250mm spacing between rungs for greater comfort (knee on the 3rd rung)
- The footpad caps are drilled so that professionals can use a carpenter's nail to fix the ladder into the ground
- Easy to use with its rope-operated system (UV-treated rope)
- The ribbed profile of the uprights makes them easy to handle for precise installation
- When the sections are deployed, rungs are in line and form a real step under

the user's feet



PLATINIUM 500 THREE-SECTION ROPE-OPERATED LADDER

Reference		(m)		(m)		(m)		(m)		(m)		(mm)		(kg)	
02533311	3x11	3	7	3.9	7.9	0.7	1.35	76	31,4	3178740162818					
02533313	3x13	3,5	8,5	4.4	9.4	0,7	1.35	76	35,5	3178740162825					
02533318	3x18	4.74	11.24	5.65	12.14	0,7	1.35	90/91/90	47,9	3178740162849					
02533320	3x20	5.25	12.75	6.15	13.65	0,7	1.35	101/103/101	59,7	3178740162856					

									
Number of rungs / steps	Folded product height (m)	Max. height of deployed product (m)	Min. access height (m)	Max. access height (m)	Product width without stabilisers (m)	Product width without stabilisers (m)	Upright section (mm)	Weight (kg)	Barcode