


NEOLIUM 200 BOX

HIGH-PERFORMANCE WELDED ALUMINIUM

The Neolium 200 box is an aluminium scaffold tower featuring a welded aluminium structure with uprights and rungs with a diameter of 50 mm. It has a one-piece platform with integrated toe boards and cross-braced guardrails. Its 200 mm diameter wheels are adjustable every 12.5 mm over a range of 175 mm.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface / Level offset / Uneven surface
Material	Aluminium
Maximum load (kg/m ²)	200
Guarantee (year)	5
Standard	EN 1004-1
Decree	2004-924



Platform with integrated toe boards



Advanced guardrails



Anti-slip and swivelling stabilisers



Castor wheels Ø 200mm adjustable up to 175mm and every 12.5mm



Cross-brace attachment jaw



Welded aluminium scaffold tower, Ø 50mm uprights



Work in level offset



Access cradle for greater safety





Model shown: 02921504

- One-piece guardrail system with diagonals
- Ø 200mm wheels with high-power locking and millimetre adjustment every 12.5mm up to 175mm
- Single-piece platform with integrated 150mm aluminium toeboards
- Access cradle for greater safety
- Work with level offset



NF certified product: Certifying body: AFNOR Certification, 11, rue Francis de Pressensé, F-93571 La Plaine Saint Denis Cedex (FR). Certification framework: Construction site equipment NF (NF096) available at www.marque-nf.com. The NF mark certifies compliance with the EN 1004-1 standard and with the NF096 framework. All rights reserved, non-contractual images.



NEOLIUM 200 BOX

Reference	Nb of platform								Neolium cross-brace lg 2.00m 02927420	Neolium rail lg 2.00 m 02927520	Neolium access cradle 02927801	Neolium tray floor 2 m 02927120	Neolium single wheel width 02927800	NEOLIUM SAFETY GR LG 2.00 M 02927620	Neolium base ladder 02927007	Neolium stabiliser 2 to 6m 02927701	Neolium extension 1m 02927004	Neolium extension 2m 02927008	Neolium exten. stab 8 to 12m 02927702		
02921502	1	3.13	2.26	0.92	4.66	3.42	2	4	108	2	2	1	1	4	2	2	4	2	0	3534740165813	
02921504	2	5.13	2.26	0.92	4.66	3.42	4	6	158	2	2	1	2	4	4	2	4	2	0	3534740165820	
02921506	3	7.13	2.26	0.92	4.66	3.42	6	8	209	2	2	1	3	4	6	2	4	2	0	3534740165837	
02921508	4	9.13	2.26	0.92	5.9	4.71	8	10	277	2	2	1	4	4	8	2	4	2	6	4	3534740165844
02921510	5	11.13	2.26	0.92	5.9	4.71	10	12	327	2	2	1	5	4	10	2	4	2	8	4	3534740165851
02921512	6	13.13	2.26	0.92	5.9	4.71	12	14	379	2	2	1	6	4	12	2	4	2	10	4	3534740165868
09074000				Tool holder					0.2	0	0	0	0	0	0	0	0	0	0	8711563239692	

								
Max. overall product height (m)	Overall length without stabilisers (m)	Product width without stabilisers (m)	Overall length with stabilisers (m)	Overall width with stabilisers (m)	Max. platform height (m)	Max. working height (m)	Weight (kg)	Barcode