

NEOLIUM 400 LINE

HIGH-PERFORMANCE WELDED ALUMINIUM

The Neolium 400 Line is a welded aluminium scaffold tower with sturdy uprights 50 mm in diameter. Scaffolding with braces and 2.08 x 1.32 m platforms enabling two people to work comfortably at the same time. This scaffolding is designed for highly-intensive professional use on flat or uneven ground and with level offset.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface / Level offset / Uneven surface
Material	Aluminium
Maximum load (kg/m ²)	200
Guarantee (year)	5
Standard	EN 1004-1
Decree	2004-924



150mm aluminium removable toe boards with quick installation



Braces guardrails



Anti-slip and swivelling stabilisers



Castor wheels Ø 200mm adjustable up to 175mm and every 12.5mm



Diagonal fixing jaw



Welded aluminium scaffold tower, Ø 50mm uprights



Work with level offset



Access cradle for greater safety



Model shown: 02924804

- R08-C Aluminium-Wood Comabi floor with aluminium toe boards and braces guardrails
- Wheels Ø 200mm with powerful locking system and millimetric adjustment system up to 175mm
- 150mm aluminium removable toe boards with quick installation
- Access cradle for greater safety
- Work with level offset



Work with level offset



All rights reserved, non-contractual images.

NEOLIUM 400 LINE

Reference	Nb of platform									Neolum extension double 1m 02927014	Neolum platform w/o hatch 2 m 02927220	Neolum rail lg 2.00 m 02927520	Neolum double base ladder 02927017	Neolum access cradle 02927801	Neolum stabiliser 2 to 6m 02927701	Neolum pf w- hatch 2 m 02927020	Neolum cross-b base lg 2.00m	Neolum double wheel width 02927810	Neolum toe board kit 400 02927116	Neolum extension double 2 m 02927018	Neolum cross-brace lg 2.00m 02927420	Neolum exten. stab 8 to 12m 02927702	
02924802	1	3.13	2.26	1.64	4.66	4.31	2	4	138	2	1	6	2	1	4	1	2	4	1	0	0	0	3534740166179
02924804	2	5.13	2.26	1.64	4.66	4.31	4	6	215	2	2	10	2	1	4	2	2	4	2	2	2	0	3534740166186
02924806	3	7.13	2.26	1.64	4.66	4.31	6	8	291	2	3	14	2	1	4	3	2	4	3	4	4	0	3534740166193
02924808	4	9.13	2.26	1.64	5.9	5.4	8	10	384	2	4	18	2	1	4	4	2	4	4	6	6	4	3534740166209
02924810	5	11.13	2.26	1.64	5.9	5.4	10	12	461	2	5	22	2	1	4	5	2	4	5	8	8	4	3534740166216
02924812	6	13.13	2.26	1.64	5.9	5.4	12	14	537	2	6	26	2	1	4	6	2	4	6	10	10	4	3534740166223
09074000					Tool holder				0,2	0	0	0	0	0	0	0	0	0	0	0	0	0	8711563239692

								
Max. overall product height (m)	Overall length without stabilisers (m)	Product width without stabilisers (m)	Overall length with stabilisers (m)	Overall width with stabilisers (m)	Max. platform height (m)	Max. working height (m)	Weight (kg)	Barcode