

NEOLIUM 600 LINE

HIGH-PERFORMANCE WELDED ALUMINIUM

The Neolium 600 Line is a welded aluminium scaffold tower with sturdy uprights 50 mm in diameter. Scaffolding with braces and 3.08 x 1.32 m platforms enabling two people to work comfortably at the same time. This scaffolding is designed for highly-intensive professional use on flat or uneven ground and with level offset.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface / Level offset / Uneven surface
Material	Aluminium
Maximum load (kg/m ²)	200
Guarantee (year)	5
Standard	EN 1004-1
Decree	2004-924



150mm aluminium removable toe boards with quick installation



Braces guardrails



Anti-slip and swivelling stabilisers



Castor wheels Ø 200mm adjustable up to 175mm and every 12.5mm



Cross-brace attachment jaw



Welded aluminium scaffold tower, Ø 50mm uprights



Work with level offset



Access cradle for greater safety



Model shown: 02926808

- R08-C Aluminium-Wood Comabi floor with aluminium toe boards and braces guardrails
- Wheels Ø 200mm with powerful locking system and millimetric adjustment system up to 175mm
- 150mm aluminium removable toe boards with quick installation
- Access cradle for greater safety
- Work with level offset



Work with level offset



All rights reserved, non-contractual images.

NEOLIUM 600 LINE

Reference	Nb of platform									Neolium platform w/o hatch 3 m 02927230	Neolium extension double 1m 02927014	Neolium crossbrace base L3 00m	Neolium double wheel width 02927810	Neolium double base ladder 02927017	Neolium access cradle 02927801	Neolium platform with hatch 3m	Neolium stabiliser 2 to 6m 02927701	Neolium rail ig 3.00 m 02927530	Neolium toe board kit 600 02927117	Neolium extension double 2 m 02927018	Neolium cross-brace ig 3.00m 02927430	Neolium exten. stab 8 to 12m 02927702	
02926802	1	3.13	3.26	1.64	5.61	4.31	2	4	158	1	2	2	4	2	1	1	4	6	1	0	0	0	3534740166230
02926804	2	5.13	3.26	1.64	5.61	4.31	4	6	253	2	2	2	4	2	1	2	4	10	2	2	2	0	3534740166247
02926806	3	7.13	3.26	1.64	5.61	4.31	6	8	349	3	2	2	4	2	1	3	4	14	3	4	4	0	3534740166254
02926808	4	9.13	3.26	1.64	6.9	5.4	8	10	460	4	2	2	4	2	1	4	4	18	4	6	6	4	3534740166261
02926810	5	11.13	3.26	1.64	6.9	5.4	10	12	556	5	2	2	4	2	1	5	4	22	5	8	8	4	3534740166278
02926812	6	13.13	3.26	1.64	6.9	5.4	12	14	651	6	2	1	4	2	1	6	4	26	6	10	10	4	3534740166285
09074000									0.2	0	0	0	0	0	0	0	0	0	0	0	0	0	8711563239692

								
Max. overall product height (m)	Overall length without stabilisers (m)	Product width without stabilisers (m)	Overall length with stabilisers (m)	Overall width with stabilisers (m)	Max. platform height (m)	Max. working height (m)	Weight (kg)	Barcode