


GOLIATH


HARD-WEARING SCAFFOLDING

The Goliath is a galvanised steel scaffold tower with 45 mm uprights and 110 x 60 cm steel platforms, giving it unrivalled sturdiness. Its base and one-piece guardrails make assembling it easy and safe. It is equipped with two gates for access from the outside.


Class	Professional
Use frequency	Ultra intensive
Use	Flat surface
Material	Steel
Maximum load (kg/m ²)	200
Guarantee (year)	5
Decree	2004-924




Craneable




Diagonals fastening




Transport base




Wheels blocking




Double platform



Rolling transport base




Stabilisers fastening



Access gate



- The GOLIATH is specially designed for building and public works and can be lifted by crane
- Heavy-duty scaffolding with Ø45 mm welded galvanised steel uprights
- Quick to assemble with few components, and no screws or tools required
- Double steel platform
- Two one-piece fall protection guardrails for safe installation
- The practical base is designed to be used as a transport trolley
- Four Ø160 mm steerable self-locking wheels



GOLIATH

Reference	Nb of platform	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (kg)	
03144001	1	2.03	1.25	0.71	2.4	1.94	1	3	79,9	3534740151083
03144002	1	2.93	1.25	0.71	2.4	1.94	2	4	96,6	3534740151090
09074000	Tool holder								0,2	8711563239692

 Max. overall product height (m)	 Overall length without stabilisers (m)	 Product width without stabilisers (m)	 Overall length with stabilisers (m)	 Overall width with stabilisers (m)	 Max. platform height (m)	 Max. working height (m)	 Weight (kg)	 Barcode
--	---	--	--	---	---	--	--	--