

GENERIS 450 TOWER

XXL COMFORT FOR WORKING AT HEIGHTS OF UP TO 18.30 M

The Generis 450 galvanised steel tower has a wide platform measuring 290 x 146 cm, which allows it to hold bulky objects and store equipment. Furthermore, its 200 mm wheels with millimetric adjustment system and its platform adjustable in one metre intervals mean this platform can be adjusted to suit any surface.


Class	Professional
Use frequency	Intensive
Use	Flat surface / Level offset
Material	Steel
Maximum load (kg/m ²)	200
Guarantee (year)	2
Decree	2004-924



Standard platforms compatible with COMABI fixed scaffolding



4.5 m² of working area



Platform adjustment every metre



370 mm adjustable screw-in feet



Single-piece frames: high degree of rigidity in the structure



Model shown: 04100048

- Simplified assembly with one-piece frames
- Extension metre by metre for assembly in complete safety
- Standard 3.00 m platforms compatible with COMABI fixed scaffolding
- Compatible with R200 and M368 structures
- Large work area
- One-piece frames for quick and easy installation
- Galvanised steel: increased stability and durability
- Millimetric wheel adjustment system over a 37 cm range
- Ø250 mm locking wheels
- Total authorised load 500 kg



GENERIS 450 TOWER

Reference	Nb of platform								Weight (kg)	Stabiliser 00005535	Mobile tower frame 1mx1.50m 04100901	Gcm 3mx0.50m mobile tower 04100902	04010320	00010915	04010335	Toe board 1625 for 2 pfs 04100907	Mobile tower foot with wheel 04100903	Mobile tower uprt 1m 4 sockets 04100904	Pc 993 side toeboard 3m blue 00015685	Mobile tower adjust strik cross-b 04100905	00080450	Toe board tower 796 for 1 plt 04100908	Accessory for stab S1 to S2 00005540	Apollo mount stabilizing arm 00005230	
04100038	1	3,3	3.11	1.61	4.82	3.33	2,3	4,3	292	4	4	4	1	4	1	2	4	4	2	1	8	0	0	0	3534740130514
04100048	1	4,3	3.11	1.61	4.82	3.33	3,3	5,3	353	4	6	5	6	1	4	1	2	4	4	2	1	12	0	0	3534740130828
04100039	2	5,3	3.11	1.61	4.82	3.33	4,3	6,3	465	4	8	7	8	1	4	2	2	4	4	4	1	16	2	0	3534740130521
04100040	3	7,3	3.11	1.61	5.75	4.26	6,3	8,3	647	4	12	10	12	1	4	3	2	4	4	6	2	24	4	0	3534740130538
04100041	4	9,3	3.11	1.61	5.75	4.26	8,3	10,3	820	4	16	13	16	1	4	4	2	4	4	8	2	32	6	0	3534740130545
04100042	5	11,3	3.11	1.61	7.52	6.02	10,3	12,3	1002	4	20	16	20	1	4	5	2	4	4	10	3	40	8	4	3534740130552
04100043	6	13,3	3.11	1.61	7.52	6.02	12,3	14,3	1207	4	24	19	24	1	4	6	2	4	4	12	4	48	10	4	3534740130569
04100044	7	15,3	3.11	1.61	7.52	6.02	14,3	16,3	1381	4	28	22	28	1	4	7	2	4	4	14	4	56	12	4	3534740130576
04100045	8	17,3	3.11	1.61	7.52	6.02	16,3	18,3	1615	4	32	25	32	1	4	8	2	4	4	16	5	64	14	4	3534740130583

 Max. overall product height (m)
  Overall length without stabilisers (m)
  Product width without stabilisers (m)
  Overall length with stabilisers (m)
  Overall width with stabilisers (m)
  Max. platform height (m)
  Max. working height (m)
  Weight (kg)
  Barcode