

GENERIS 900 TOWER


THE HIGH-LEVEL PLATFORM

The Generis 900 galvanised steel tower has a wide platform measuring 290 x 290 cm, which allows it to hold bulky objects and store equipment. Furthermore, its 200 mm wheels with millimetric adjustment system and its platform adjustable in one metre intervals mean this platform can be adjusted to suit any surface.

Class	Professional
Use frequency	Intensive
Use	Flat surface / Level offset
Material	Steel
Maximum load (kg/m ²)	200
Guarantee (year)	2
Decree	2004-924



- Simplified assembly with one-piece frames
- Extension metre by metre for assembly in complete safety
- Standard 3.00 m platforms compatible with COMABI fixed scaffolding
- Compatible with R200 and M368 structures
- Large platform with 9 m² platform surface area
- Freestanding up to a working height of 8.30 m
- Millimetric wheel adjustment system over a 37 cm range
- Galvanised steel: increased stability and durability
- Ø250 mm locking wheels
- Total authorised load 500 kg
- Up to a working height of 20.30 m



GENERIS 900 TOWER very large
working surface: 3.00 x 3.00 m

GENERIS 900 TOWER

Reference	Nb of platform										Mobile tower frame 1mx3m 04100900	00010520	Gcm 3mx0.50m mobile tower 04100902	04010320	04010335	Mobile tower foot with wheel 04100903	Toe board 3100 for 4 pfs 04100906	Mobile tower uprt 1m 4 sockets 04100904	Rc993 side toeboard 3m blue 00015685	Mob tower adjust strik cross-b 04100905	00080450	toe board tower 796 for 1 pit 04100908	S1 stabiliser 00005535	Accessory for stab S1 to S2 00005540	
04100029	1	3,3	3,14	3,14	3,14	3,14	2,3	4,3	347		4	8	4	3	1	4	2	4	2	1	8	0	0	0	3534740130422
04100047	1	4,3	3,14	3,14	3,14	3,14	3,3	5,3	422		6	9	6	3	1	4	2	4	2	1	12	0	0	0	3534740130811
04100030	2	5,3	3,14	3,14	3,14	3,14	4,3	6,3	547		8	11	8	3	2	4	2	4	4	1	16	2	0	0	3534740130439
04100031	3	7,3	3,14	3,14	3,14	3,14	6,3	8,3	755		12	14	12	3	3	4	2	4	6	2	24	4	0	0	3534740130446
04100032	4	9,3	3,14	3,14	4,82	4,82	8,3	10,3	955		16	17	16	3	4	4	2	4	8	2	32	6	4	0	3534740130453
04100033	5	11,3	3,14	3,14	4,82	4,82	10,3	12,3	1200		20	20	20	3	5	4	2	4	10	3	40	8	4	0	3534740130460
04100034	6	13,3	3,14	3,14	4,82	4,82	12,3	14,3	1408		24	23	24	3	6	4	2	4	12	4	48	10	4	0	3534740130477
04100035	7	15,3	3,14	3,14	4,82	5,75	14,3	16,3	1607		28	26	28	3	7	4	2	4	14	4	56	12	4	4	3534740130484
04100036	8	17,3	3,14	3,14	4,82	5,75	16,3	18,3	1839		32	29	32	3	8	4	2	4	16	5	64	14	4	4	3534740130491
04100037	9	19,3	3,14	3,14	4,82	5,75	18,3	20,3	2047		36	32	36	3	9	4	2	4	18	6	72	16	4	4	3534740130507

								
Max. overall product height (m)	Overall length without stabilisers (m)	Product width without stabilisers (m)	Overall length with stabilisers (m)	Overall width with stabilisers (m)	Max. platform height (m)	Max. working height (m)	Weight (kg)	Barcode