

DOUBLE INSULATED LADDER

HIGH-PERFORMANCE, WITH THE ADDED BONUS OF INSULATION

The freestanding double insulated ladder with fibreglass uprights.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface
Main material	Mixed aluminium/fibreglass
Maximum load (kg)	150
Guarantee (year)	2
Standard	EN 131
Standard requirements	Electrical test in compliance with EN 50528 (2010)
Decree	96-333
Recyclable up to (%)	40

The EN 50528 (2010) standard sets out the values that guarantee users against low-voltage currents under 1000 volts AC or 1500 volts DC. The breakdown test is 10,000 volts.
Produktionsvorschriften Certificate C901062. AFS 2004:3 Certificate C901061. SS 2091 edition 4
Certificate C901061. Tested and certified by RISE.



Bucket hook



Ribbed anti-slip footpads



Model shown: 04255008

- Fibreglass uprights protecting users against electric shocks
- Aluminium steps 80 mm wide for lighter weight
- Retaining straps



Electricity
Telephony



All rights reserved, non-contractual images.



DOUBLE INSULATED LADDER

Reference		 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (mm)	 (kg)	
04255004	4	1,1	1.02	1.92	0.2	0.46	1	66	7,5	3178740020187
04255006	6	1,6	1.48	2.38	0.2	0.51	1.38	66	10.4	3178740020194
04255008	8	2,1	1.94	2.84	0.2	0.56	1.75	66	14,1	3178740020200
04255010	10	2,6	2.41	3.31	0.2	0.61	2.13	66	17,8	3178740023591
04255012	12	3,1	2.88	3.78	0.2	0.66	2,5	66	21,5	3178740023607
04255014	14	3,6	3.34	4.24	0.2	0.71	2.87	66	25,2	3178740023614

									
Number of rungs / steps	Folded product height (m)	Max. overall product height (m)	Max. access height (m)	Thickness of folded product (m)	Product width at base (m)	Base width (m)	Upright section (mm)	Weight (kg)	Barcode