

TWO-SECTION INSULATED PUSH-UP LADDER

MEDIUM HEIGHT, WITH THE ADDED BONUS OF INSULATION

The mixed aluminium/fibreglass two-section push-up ladder features a stabiliser bar with reinforced footpads, safety hooks and extension wheels guaranteeing safety and ease of use.


Class	Professional
Use frequency	Ultra intensive
Use	Flat surface
Main material	Mixed aluminium/fibreglass
Maximum load (kg)	150
Guarantee (year)	2
Standard	EN 131
Standard requirements	Electrical test in compliance with EN 50528 (2010)
Decree	96-333
Recyclable up to (%)	29

The EN 50528 (2010) standard sets out the values that guarantee users against low-voltage currents under 1000 volts AC or 1500 volts DC. The breakdown test is 10,000 volts.


Produktionsvorschriften Certificate C901062. AFS 2004:3 Certificate C901061. SS 2091 edition 4 Certificate C901061. Tested and certified by RISE.




Wide base with reinforced footpads for increased stability



Sliding section locking system



Guide wheels



Optional cradle fibreglass support



Model shown: 04322408

- Complete insulation against electric shocks
- Aluminium rungs for lighter weight
- Simple, intuitive handling
- Polyamide insert to prevent any jamming when sliding the second section into position



Electricity
Telephony



All rights reserved, non-contractual images.

TWO-SECTION INSULATED PUSH-UP LADDER

Reference		 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (mm)	 (kg)	
04322408	2x8	2.41	4.18	3.31	5.08	0.43	0.81	66	10.9	3178740162511
04322410	2x10	2.97	5.3	3.87	6.2	0.43	0.91	66	13	3178740162528
04322412	2x12	3.53	6.14	4.43	7.04	0.43	1.01	66	15	3178740162535
09022004 	Cradle fibreglass support								0.65	3178740031497

Products delivered shrink-wrapped.

 Reference on request

									
Number of rungs / steps	Folded product height (m)	Max. height of deployed product (m)	Min. access height (m)	Max. access height (m)	Product width without stabilisers (m)	Overall width with stabilisers (m)	Upright section (mm)	Weight (kg)	Barcode