MONTANA

THE HIGH-PERFORMANCE LADDER LIFTS

The Montana is our most powerful ladder lift featuring aluminium ladders! Its winch can be detached from the structure for transport and safety. Its motor can lift up to 200 kg to a height of up to 32 metres.
A version is available with a knee brace included to adapt to all configurations encountered on worksites.
When in the vertical position, the ladder lift can also be used as a single ladder.

Use frequency	Intensive
Main material	Aluminium
Maximum load (kg/m²)	200
Guarantee (year)	2
Standard	NF EN 12158-2
Standard requirements	Complies with the Machinery Directive 2006-42-EC



Detachable winch for added safety (no theft risk)



Bend section 0° to 60°



MULTI-configurable case: 12 possible configurations with the "MODULARITY+" pack



Removable link plates



MULTI-configurable case: 12 possible configurations with the 'MODULARITY' pack

MADE IN FRANCE



Model presented: 05022900

All rights reserved, non-contractual images.

- Lift 200 kg to a height of 32 metres.
- Semi-automatic coupling of the winch and contents (crates, skips, etc.) for quick and reliable installation.
- 0–60° folding ladder suitable for both rural and urban settings. The 0° position converts it into a simple ladder. Secure locking mechanism thanks to ribbed rungs.
- The trolley is positioned once the structure has been raised.
- Vertical loading possible on R200-frame façade scaffolding and M368 multidirectional scaffolding.

Construction finishing work

Construction structural building work

Finishing decoration painting

Maintenance

Structural work roofing



Model presented: 05022926









MONTANA

Reference	Description	(kg)	
05022926 ⦸	Montana 9m base	155	3534740114163
05022900	10m with a box and a knee pad	195	3534740114088
05022919 ⦸	13m drywall specialist pack	337	3534740114170
05022918	Montana pack modularity plus	36	3534740114118
05022927	Montana drywall spclst pack	80	3534740114132
05022932	Montana modularity pack	18	3534740114095

⦸ Reference on request

Weight (kg)

Barcode

Features:

- Ladder 2.00m - only 12kg
- Oblong rungs
- Load capacity including vertical 200kg
- Knee joint adjustment 0 to 60°
- Usable length 32.00m
- Working angle relative to the ground 30 to 90°
- Lifting speed 22m/min
- Winch: 1100 W – 230 V single-phase - electronic control board
- Cable length 65.00m - Ø 5mm
- 24 V detachable remote control
- Lower limit switch on removable stop
- Upper limit switch: by electric sensor
- Safety: automatic cable slack prevention
- Power cable required (not supplied): < 25m - 3 x 2.5mm²