

R'LIFT 420 X


ELEVATION WITHIN REACH

The R'LIFT X range provides a high level of ergonomics, productivity and safety. Providing safety from the ground and for use outdoors, the R'LIFT X is a workstation that is appreciated by users, factory managers, site managers and QHSE managers.

Use frequency	Ultra intensive
Use	Flat surface
Main material	Steel
Maximum load (kg)	150
Guarantee (year)	2
Standard	EN 280
Standard requirements	Machinery Directive 2006/42/EC - R486
Maximum manual force (kNh)	200

According to recommendation R486, the CACES (French Certificate of Aptitude for Safe Driving) should be used as training/verification of acquired knowledge in order to provide the employee with the driving authorisation necessary for using these products.


A six-monthly inspection of products should be carried out by a designated competent person or competent authority.



Integrated tool tray



Folding access step



Integrated spirit level with markings



Steering wheel for assisted manual lifting



Front wheels with brake



Integrated lifting rings



Transportable with a forklift/pallet truck



- Safety from the ground
- Steel guardrail with cage
- Ready to use, operates without power using a patented gas spring system
- Intuitive and effortless for maximum protection against ergonomic risks
- Means you are always working at the right height
- Easy to move around on site
- 0.85 x 0.64 m platform
- 200 mm front wheels with brake and 250 mm rear wheels
- Steering ratio: maximum elevation in a few rotations

- Designed for outdoor use
- Craneable and moveable by forklift / pallet truck
- Allows a tilt of 3° (<5.3%) during use, refer to the integrated spirit level



Construction finishing work





Maintenance



Site equipment



Store shelving



R'LIFT 420 X

Reference	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (kg)	
05026003	1.95	3.46	0.69	2.2	2.69	4.2	0.95	382	3178740263843

 Min. height of de- ployed product (m)	 Max. height of de- ployed product (m)	 Min. platform height (m)	 Max. platform height (m)	 Min. working height (m)	 Max. working height (m)	 Product width wit- hout stabilisers (m)	 Weight (kg)	 Barcode
---	---	--	--	---	---	---	--	--