

MOBILE FALL ARRESTERS

This fall prevention unit is a glider. It can be used on any part of the rope for vertical movements. It will clamp in the event of an uncontrolled fall, sliding or decent and will in extreme cases allow rappelling down the rope (while awaiting rescue). It is equipped with a voluntary locking system. Opening the device by hand lets the user remove the rope from the glider. This opening is articulated and closes with a double lock. The rope cannot come out of its housing thanks to the top latch and the lower cam that once attached to the carabiner limits travel. Part of the fall prevention system components.



- ▶ A steel fall prevention mechanism
- ▶ A product with two functions: glider and clamp
- ▶ Compatible with our 11 mm diameter safety rope
- ▶ For frequent use
- ▶ It connects to the harness sternal or dorsal anchor points
- ▶ It follows the user's motion and clamps in the event of a fall
- ▶ *Compliant with standard EN 353-2 (with 11 - 12 mm rope diameters)
- ▶ *Compliant with standard EN 358 (with 12 - 12.5 mm rope diameters)

Product characteristics	
Material	Steel
Warranty (years)	5

To comply with the law and be sure to use equipment in perfect condition, all fall prevention PPE must be inspected every year and before use, always carry out a visual check. UNYC® personal protective equipment come with a 10-year guarantee from the date of manufacture and a 5-year guarantee from the date of initial use.

Ref.	Des.	Weight (kg)	CE	EAN barcode
09100201	Mobile fall arresters	0.214	CE	3178740209353