SINGLE-SECTION LADDER

THE SIMPLE, ROBUST LADDER

Ultra-pro single-section ladder, sturdy, practical and compact, ideal for accessing heights in complete safety.

Class	Professional
Use frequency	Intensive
Use	Flat surface
Main material	Aluminium
150 (kg)	150
4 (year)	4
Standard	EN 131
Decree	96-333

The stabiliser bar is supplied unassembled, but with all the necessary screws and instructions.



Anti-slip ribbed footpads



280mm rung spacing



Anti-slip ribbed footpads



Rungs attached by crimping, non-separable and unalterable. Rectangular uprights with a width



30 x 30 mm anti-slip ribbed square rungs



Anti-slip ribbed footpads (models under 3 metres)



Model shown: 11210110

MADE IN FRANCE

All rights reserved, non-contractual images.

- Ultra-strong: rungs are fixed by crimp-fitting and cannot be dismantled or distorted. Rectangular uprights 22mm wide.
- Stable: non-slip notched footpads (models under 3 metres). Anti-slip notched end caps. Stabilizing base with non-slip footpads (models over 3 metres).
- Comfortable: 30 x 30mm anti-slip crimped square rungs.
- Easy access: distance between rungs 28cm

SINGLE-SECTION LADDER

Reference		(m)	(m)	(cm)	(m)	(m)	(mm)	(kg)	
11210108 ⊘	8	2.27	**3.17**	5,6	0.35		56	3,3	3178740196592
11210110 ⊘	10	2.83	**3.73**	5,6	0.35		56	4,1	3178740196615
11210114 ⊘	14	4	**4,9**	5,6	0.35	0.81	66	7,3	3178740196639

According to standard EN 131, only folded ladders over 3 metres long are required to have a system for widening the base.

⊘ Reference on request

Number of rungs / steps	Max. overall product height (m)	Max. access height (m)	Thickness of folded product (m)	Product width without stabilisers (m)	Product width with stabiliser bar (m)	Upright section (mm)	Weight (kg)	Barcode