

TOTEM LINE 180

THE ALUMINIUM SCAFFOLD TOWER, THE PROFESSIONALS' CHOICE

The Totem 2 Line 180 is an aluminium scaffold tower. Its patented Ergoblock connection system ensures reliable locking in a single movement. Its 150 mm detachable aluminium toe boards are quick to fit, with no need for screws or tools. Its 200 mm diameter wheels are adjustable every 12.5 mm over a range of 175 mm.


Class	Professional
Use frequency	Ultra intensive
Use	Flat surface / Level offset / Uneven surface
Material	Aluminium
Maximum load (kg/m ²)	200
Guarantee (year)	5
Standard	EN 1004-1
Standard requirements	Recommendation R 457
Decree	2004-924
Recyclable up to (%)	85



Ergoblock® single movement locking system




One-piece guardrails



Wheels Ø 200mm adjustable up to 175mm up to 12.5mm increments



Access cradle for greater safety




Easy assembly of the detachable aluminium toeboards, doesn't require any screws



Model shown: 22403650

- High-resistance, anti-rotation rung crimping
- The connection between the railings is original, very simple and safe
- The Ergoblock® system on the stabilisers and guardrails can be closed with one hand and adjusted to ensure the best possible fit
- The aluminium/wood platform is fitted with an access hatch from the inside and 4 mobile toeboards to make the platform easier to store
- Ribbed jaws of cross-braces: simple placement and highly reliable connection
- The large-diameter wheels are designed to cope with obstructed floors on all types of site

- The length of the stabilisers can be adjusted to suit different heights. Integrated level offset.
- Single-piece and cross-braced guardrail "X'UP": for very quick, safe installation and saves time during assembly and disassembly
- Quick-fit 150 mm detachable aluminium toe boards
- Toe boards fitted without screws or tools



NF certified product: Certifying body: AFNOR Certification, 11, rue Francis de Pressensé, F-93571 La Plaine Saint Denis Cedex (FR). Certification framework: Construction site equipment NF (NF096) available at www.marque-nf.com. The NF mark certifies compliance with the EN 1004-1 standard and with the NF096 framework. All rights reserved, non-contractual images.

TOTEM LINE 180

Reference	Nb of platform									Wide-base ladder 0.78 m 20403010	A-S Totem line 180 platform 20403056	Secure brace L 180 m 20400032	Unit wheel foot kit 20400006	Access cradle 02900010	Cross-brace L 2.193 m 20400042	Totem stabiliser 20400021	Single-piece guardrail - 1.8 m 20400062	Extension 1m W 0m80 20403011	A-S Totem line 180 toeboard 20403058	Extension 2m W 0m780 20403013	Stabilisers 7.8 m 20400023	
22403620 	1	3	2.11	0,9	4,5	3,8	1.85	3.85	73,5	2	1	2	4	1	2	4	2	2	1	0	0	3178740118631
22403630	1	4	2.11	0,9	4,5	3,8	2.85	4.85	79	2	1	2	4	1	2	4	2	2	1	1	0	3178740118648
22403640 	2	5	2.11	0,9	4,5	3,8	3.85	5.85	110,1	2	2	2	4	1	2	4	4	2	2	2	0	3178740118655
22403650	2	6	2.11	0,9	4,5	3,8	4.85	6.85	115,5	2	2	2	4	1	2	4	4	2	2	3	0	3178740118662
22403660	3	7	2.11	0,9	4,5	3,8	5.85	7.85	148,6	2	3	2	4	1	2	4	6	2	3	4	0	3178740118679
22403670 	3	8	2.11	0,9	5	5,3	6.85	8.85	162,2	2	3	2	4	1	2	4	6	2	3	5	4	3178740118686
22403680	4	9	2.11	0,9	5	5,3	7.85	9.85	196	2	4	2	4	1	2	4	8	2	4	6	4	3178740118693
09074000									0,2	0	0	0	0	0	0	0	0	0	0	0	0	8711563239692

 Reference on request

								
Max. overall product height (m)	Overall length without stabilisers (m)	Product width without stabilisers (m)	Overall length with stabilisers (m)	Overall width with stabilisers (m)	Max. platform height (m)	Max. working height (m)	Weight (kg)	Barcode