

TOTEM LINE 250

THE ALUMINIUM SCAFFOLD TOWER, FOR COMFORT AND SPACE

The Totem 2 Line 250 is an aluminium scaffold tower. Its patented Ergoblock connection system ensures reliable locking in a single movement. Its 150 mm detachable aluminium toe boards are quick to fit, with no need for screws or tools. Its 200 mm diameter wheels are adjustable every 12.5 mm over a range of 175 mm.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface / Level offset / Uneven surface
Material	Aluminium
Maximum load (kg/m ²)	200
Guarantee (year)	5
Standard	EN 1004-1
Standard requirements	Recommendation R 457
Decree	2004-924
Recyclable up to (%)	86



Ergoblock® single movement locking system



Easy assembly, doesn't require any screws or tools




One-piece guardrails



Ø 200mm lockable wheels, adjustable to 175mm and every 12.5mm



Access cradle for greater safety



Platform (inside)
2.41 x 0.65m



Model shown: 22403760



NF certified product: Certifying body: AFNOR Certification, 11, rue Francis de Pressensé, F-93571 La Plaine Saint Denis Cedex (FR). Certification framework: Construction site equipment NF (NF096) available at www.marque-nf.com. The NF mark certifies compliance with the EN 1004-1 standard and with the NF096 framework. All rights reserved, non-contractual images.

- High-resistance, anti-rotation rung crimping
- The connection between the railings is original, very simple and safe
- The Ergoblock® system on the stabilisers and guardrails can be closed with one hand and adjusted to ensure the best possible fit
- The aluminium/wood platform is fitted with an access hatch from the inside and 4 mobile toeboards to make the platform easier to store
- Ribbed jaws of cross-braces: simple placement and highly reliable connection
- The large-diameter wheels are designed to cope with obstructed floors on all types of site

- The length of the stabilisers can be adjusted to suit different heights. Integrated level offset.
- Single-piece and cross-braced guardrail "X'UP": for very quick, safe installation and saves time during assembly and disassembly
- Quick-fit 150 mm detachable aluminium toe boards
- Toe boards fitted without screws or tools
-

TOTEM LINE 250

Reference	Nb of platform									Wide-base ladder 0.78 m 20403010	Base L 250 m 20400033	A-S Totem line 250 platform 20403057	Unit wheel foot kit 20400006	Access cradle 02900010	A-S Totem 250 cross-brace 20403060	A-S Totem line 250 toeboard 20403059	Totem stabiliser 20400021	Single-piece guardrail L 2.5 m 20400063	Extension 1 m W 0m80 20403011	Extension 2 m W 0m780 20403013	Stabilisers 78 m 20400023	
22403720	1	3	2.81	0.9	4.6	4.3	1.85	3.85	85.7	2	2	1	4	1	2	1	4	2	2	1	0	3178740118709
22403730	1	4	2.81	0.9	4.6	4.3	2.85	4.85	91.2	2	2	1	4	1	2	1	4	2	2	1	0	3178740118716
22403740	2	5	2.81	0.9	4.6	4.3	3.85	5.85	131	2	2	2	4	1	2	2	4	4	2	2	0	3178740118723
22403750	2	6	2.81	0.9	4.6	4.3	4.85	6.85	136.4	2	2	2	4	1	2	2	4	4	2	3	0	3178740118730
22403760	3	7	2.81	0.9	4.6	4.3	5.85	7.85	176.2	2	2	3	4	1	2	3	4	6	2	4	0	3178740118747
22403770	3	8	2.81	0.9	5.3	5.5	6.85	8.85	188.7	2	2	3	4	1	2	3	4	6	2	5	4	3178740118754
22403780	4	9	2.81	0.9	5.3	5.5	7.85	9.85	231.6	2	2	4	4	1	2	4	4	8	2	6	4	3178740118761
09074000	Tool holder								0.2	0	0	0	0	0	0	0	0	0	0	0	0	8711563239692

☉ Reference on request

								
Max. overall product height (m)	Overall length without stabilisers (m)	Product width without stabilisers (m)	Overall length with stabilisers (m)	Overall width with stabilisers (m)	Max. platform height (m)	Max. working height (m)	Weight (kg)	Barcode