

X'TOWER

PARA SUS OBRAS X'TREMAS

This telescopic scaffold tower is the scaffolding all-rounder, whatever it is used for. A complete patented tool made in France complying with the regulations. Its height can be adjusted every 25 cm. Its compactness makes it very easy to move. Its one-piece structure allows it to be erected and dismantled safely by one person in less than three minutes. It will satisfy all types of need.


Class	Professional
Use frequency	Intensive
Use	Flat surface / Level offset
Main material	Aluminium
Maximum load (kg/m²)	200
Guarantee (year)	2
Standard	EN 1004-1
Decree	2004-924
Recyclable up to (%)	84



Reinforced aluminium locking device with automatic return



Toe board locking system



Handle for adjustment and locking



Wheels Ø 150mm. Adjustable up to 125mm in 25mm increments



Optional Embarq kit



Model shown: 22405530

- Easy assembly by just one person
- Moved on four lockable wheels
- 1.55 x 0.60m anti-slip platform and access trapdoor opening inside the scaffolding
- Two models, working height 4 m or 4.80m
- Platform height adjustable every 25cm
- Foldable toe boards integrated to the platform
- Safe assembly and disassembly
- Two foldable one-piece guardrails
- Four individually foldable stabilisers with millimetric adjustment system
- Dimensions when folded: H 1.34/1.35 x W 0.97 x L 0.90/0.98 m
- The Embarq kit is sold as an option (ref. 20405100). It is strongly recommended to facilitate the storage of the X'Tower in vehicles.



Construction finishing work



Maintenance



Finishing decoration painting



X'TOWER

Reference	Nb of platform	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (kg)	
22405520	1	3.1	1.77	0.87	2.66	2.41	1.35	0.97	0.9	1.3	2.06	3.3	4.06	66	3178740162009
22405530	1	3.85	1.67	0.88	2.56	2.4	1.34	0.97	0.98	1.3	2.81	3.3	4.81	73	3178740162016
20405100	Embarq kit loading aid													2,3	3178740168971

 Max. overall product height (m)	 Overall length without stabilisers (m)	 Product width without stabilisers (m)	 Overall length with stabilisers (m)	 Overall width with stabilisers (m)	 Folded height (m)	 Folded width (m)	 Folded length (m)	 Min. platform height (m)	 Max. platform height (m)	 Min. working height (m)	 Max. working height (m)	 Weight (kg)	 Barcode
--	---	--	--	---	--	---	--	---	---	--	--	--	--