

TOTEM BOX 250

THE ALUMINIUM SCAFFOLD TOWER, FOR COMFORT AND SPACE

The Totem 2 Box 250 is an aluminium scaffold tower. Its patented Ergoblock connection system ensures reliable locking in a single movement. Its 150 mm detachable aluminium toe boards are quick to fit, with no need for screws or tools. Its 200 mm diameter wheels are adjustable every 12.5 mm over a range of 175 mm.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface / Level offset / Uneven surface
Material	Aluminium
Maximum load (kg/m ²)	200
Guarantee (year)	5
Standard	EN 1004-1
Standard requirements	Recommendation R 457
Decree	2004-924
Recyclable up to (%)	88



Ergoblock® single movement locking system



Easy platform assembly with ergonomic hooks



One-piece guardrails



Wheels Ø 200mm adjustable up to 175mm up to 12.5mm increments



Access cradle for greater safety



Large diameter wheels for congested floors



Model shown: 26403760



NF certified product: Certifying body: AFNOR Certification, 11, rue Francis de Pressensé, F-93571 La Plaine Saint Denis Cedex (FR). Certification framework: Construction site equipment NF (NF096) available at www.marque-nf.com. The NF mark certifies compliance with the EN 1004-1 standard and with the NF096 framework. All rights reserved, non-contractual images.

- High-resistance, anti-rotation rung crimping
- The connection between the guardrails is original, very simple and safe
- The Ergoblock® system on the stabilisers and guardrails can be closed with one hand and adjusted to ensure the best possible fit
- The aluminium/wood platform is fitted with integrated toeboards and an access hatch from the inside
- Ribbed jaws of cross-braces: simple placement and highly reliable connection
- The large-diameter wheels are designed to cope with obstructed floors on all types of site

- The length of the stabilisers can be adjusted to suit different heights. Integrated level offset
- Single-piece and cross-braced guardrail "X'UP": for very quick, safe installation and saves time during assembly and disassembly

TOTEM BOX 250

Reference	Nb of platform																									
		Wide-base ladder 0.78 m 20403010	Brace L 250 m 20400033	1 unit wheel foot kit 20400006	Access cradle 02900010	A-S Totem 250 cross-brace 20403060	Totem stabiliser 20400021	Single-piece guardrail L 2.5 m 20400063	Extension 1 m W 0m80 20403011							Totem 2-tray-floor- 250mx0.67m 02004902	Extension 2m W 0m780 20403013	Stabilisers 78 m 20400023								
26403720 	1	3	2.81	0.9	4.6	4.3	1.85	3.85	88.2	2	2	4	1	2	4	2	2	1	0	0	3178740118426					
26403730	1	4	2.81	0.9	4.6	4.3	2.85	4.85	90.4	2	2	4	1	2	4	2	2	1	1	0	3178740118433					
26403740 	2	5	2.81	0.9	4.6	4.3	3.85	5.85	129.6	2	2	4	1	2	4	4	2	2	2	0	3178740118440					
26403750	2	6	2.81	0.9	4.6	4.3	4.85	6.85	135.1	2	2	4	1	2	4	4	2	2	3	0	3178740118457					
26403760	3	7	2.81	0.9	4.6	4.3	5.85	7.85	174.4	2	2	4	1	2	4	6	2	3	4	0	3178740118464					
26403770 	3	8	2.81	0.9	5.3	5.5	6.85	8.85	190	2	2	4	1	2	4	6	2	3	5	4	3178740118471					
26403780 	4	9	2.81	0.9	5.3	5.5	7.85	9.85	229.2	2	2	4	1	2	4	8	2	4	6	4	3178740118488					
09074000				Tool holder				0.2	0	0	0	0	0	0	0	0	0	0	0	0	8711563239692					

☉ Reference on request

								
Max. overall product height (m)	Overall length without stabilisers (m)	Product width without stabilisers (m)	Overall length with stabilisers (m)	Overall width with stabilisers (m)	Max. platform height (m)	Max. working height (m)	Weight (kg)	Barcode